

Update: 21/06/2024



PLASTER PRIMER

- Enhances adhesion
- Reduces substrate absorbency
- Improves plaster application
- Prevents efflorescence
- Efficient and easy to apply
- Strengthens the substrate



Ecoprox Plaster Primer is a dispersion-based primer for thin-layer plasters, enhancing the adhesion of organic binders-based plasters to mineral substrates. It reduces and evens out substrate absorbency, facilitates plaster application and texturing. The product is water washable and has a neutral odor.

APPLICATION

Ecoprox Plaster Primer undercoat is recommended for use under organic binder plasters. It is applied onto a mesh-reinforced adhesive layer and onto strong, clean, and dry mineral substrates, concrete surfaces, as well as gypsum plasterboards and other mineral-based substrates. Suitable for interior and exterior applications.

TECHNICAL PARAMETERS

Color Options	white and tintable
Recommended number of layers:	1-2
Air and substrate application temperature:	od +5°C do +25°C
Relative air humidity::	≤ 75%
Drying time:	3-24 h
Application:	trowel, roller, brush
Brookfield viscosity at 20±2°C:	according to PN-ISO 2555: 20000÷30000 mPa•s
Density:	approximately 1.45 kg/dm³
pH:	approximately 8,16
Volatile Organic Compounds Content:	< 6g/I VOC



X PLASTER PRIMER
Update: 21/06/2024



SURFACE PREPARATION

The surface should be load-bearing, even, dry, free from stains, and free from biological and chemical efflorescence.

STORAGE

Store for 18 months from the production date in the original sealed packaging, kept at temperatures between +5°C and +25°C. Residual product should be tightly sealed and used within 3 weeks. If diluted, use entirely. Protect from frost and excessive sunlight.

HEALTH AND SAFETY RECOMMENDATIONS

Volatile Organic Compounds content: the product contains approximately 6 g/I VOC.

The paint contains biocidal products: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-4-isothaiazolin-3(2H)-one 3:1 (CAS 55965-84-9), tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazol-2,5(1H,3H)-dione (CAS 5395-50-6), 3-(3,4-dichlorophenyl)-1,1-dimethylurea (CAS: 330-54-1), Carbendazim (CAS: 10605-21-7), 2-octyl-2H-isothiazol-3-one (CAS: 26530-20-1).

May cause allergic reactions. In case of eye contamination, rinse thoroughly with plenty of water. If irritation or ingestion occurs, seek medical advice immediately. Show the label, Technical Data Sheet, and Safety Data Sheet. Protect from children.

ENVIRONMENTAL PROTECTION AND DISPOSAL

Do not pour liquid residues into drains, waterways, or soil. Dispose of empty containers for recovery or safe disposal. Additional information can be found in the current Safety Data Sheet available on the website: www.ecoprox.eu

WARRANTY AND REPORTING QUALITY ISSUES

The manufacturer guarantees that the product, when used correctly and in compliance with application requirements, achieves the desired final effect. If any irregularities are observed during application, cease work and notify the seller.

IMPORTANT INFORMATION

The data in the Technical Data Sheet is based on laboratory research and practical experience, provided with the best knowledge of the manufacturer. Product quality is ensured by our production and quality control system. Due to diverse substrates and application conditions, each Buyer/User must verify at their own risk the suitability of **ECOPROX** products for their intended purpose,



TECHNICAL DATA SHEET **ECOPROX PLASTER PRIMER**

Update: 21/06/2024

considering site-specific conditions and requirements, and adhering to technical and safety standards. We cannot control conditions under which the product is used or various factors affecting its application and utilization. We also do not assume liability for losses or damages resulting from incorrect application or improper storage, handling, and transportation of products.

As the Manufacturer, we assume the product is used by individuals with appropriate skills. The product is intended for professional use, meaning the Buyer/User has sufficient preparation to use the product while strictly observing technical and safety conditions. The Buyer/User is responsible for substrate preparation, reference application, and correct integration of the product with other companies' products. The information provided above is in good faith, based on current knowledge and practical experience. The Manufacturer reserves the right to change the content of the Technical Data Sheet without prior notice to recipients. Earlier versions of the data sheets become invalid upon release of this Technical Data Sheet. The latest versions of technical and safety data sheets are available at:

www.ecoprox.eu

